

MANUFACTURERS OF:

Industrial Oven, Furnaces, Cooling Equipments, Scientific, Surgical,& Laboratory Equipments



INSTRUMENTS & SERVICES

LOW TEMPERATURE WATER BATH(Cryo Bath) (Table Tpp Model)

Introduction: "Lab Care" make Laboratory Low Temperature

Water Bath are designed and fabricated to suit various I.S. standards application in the growing field of Medical, Agricultural Institution, Bio-Chemical Industrial, Research laboratories and Various

Industries.

Features: a) Temperature Range:-30 to 90 °C

b) Digital Temperature controller accuracy +/- 0.5 °C.



Specification:

| Models | LC 12 'D' | LC 12 'E' | LC 12 'F' |
|---|---|--------------|--------------|
| Capacity | 15 ltrs | 15 ltrs | 15 ltrs. |
| Working Temp.Range | 0 to 90°C | -20 to 90°C | -30 to 90 °C |
| Working Size (HxLXD cms | 20 x 20 x 25 | 20 x 20 x 25 | 20 x 20 x 25 |
| Full Tank Size (HxLXD cms | 20 x 20 x 45 | 20 x2 0 x 45 | 20 x 20 x 45 |
| Inner Chamber | Stainless Steel 20 swg. 304 quality | | |
| External | Mild Steel Powder Coated /Stainless Steel Grade SS:304 | | |
| Controller | Electronic Display Digital Temperature Controller. | | |
| Sensor | RTD Pt-100 | | |
| Accuracy | +/- 0.1 °C | | |
| Uniformity | +/- 0.2 °C with medium Stirring. | | |
| Cool down time | 45 min. upto 0 °C without load with respect to ambient. | | |
| Compressor | Hermetically sealed Brand New Kirloskar Compressor. | | |
| Heater | S.S.Tubler water heater | | |
| Stirring Motor | 1440 RPM top mounted. | | |
| Insulation | PUF / Glass wool 65 mm. | | |
| Lid Insulation | Thermo Cole | | |
| Safety device | Time Delay circuit for compressor | | |
| Optional | | | |
| Timer | ON / OFF cycle. | | |
| Capacity (watts) | 1500 | 2000 | 3000 |
| Power Consumption | 6 amps | 8 amps | 12 amps |
| Net weight, approx | 40 kgs | 45 kgs | 50 kgs |
| Electric requirements AC 230 V & 50 Hz cycle. | | | |

Cell: 09821544308 / 9320671406

E-mail: lab_care@rediffmail.com / rhussain11@yahoo.co.in Www.labcareindia.com / www..labcareservices.com